





```

for j=1:4;
g(j, i)=g(j, i)/s(i);
end
end

wg(1)=0;wg(2)=0;wg(3)=0;wg(4)=0;
fori=1:4;
for j=1:4;
wg(i)=wg(i)+g(i, j);
end
wg(i)=wg(i)/4;
end
lambdamax=wg(1)*s(1)+wg(2)*s(2)+wg(3)*s(3)+wg(4)*s(
4);
CI=(lambdamax-4)/3;
CR=CI/0.9;
printf('\nlambdamax at level 1 %f, lambdamax)
printf('\nconsistency ratio for comparison of the factors wrt
goal is %f, CR)
//comparison matrix for level2(with respect to the factor A
xa=[1 6 8;1/6 1 4;1/8 1/4 1];
sa(1)=0;sa(2)=0;sa(3)=0;
fori=1:3;
for j=1:3;
sa(i)=sa(i)+xa(j, i);
end
end
fori=1:3;
for j=1:3;
xa(j, i)=xa(j, i)/sa(i);
end
end

wa(1)=0;wa(2)=0;wa(3)=0;
fori=1:3;
for j=1:3;
wa(i)=wa(i)+xa(i, j);
end
wa(i)=wa(i)/3;
end
lambdamax=wa(1)*sa(1)+wa(2)*sa(2)+wa(3)*sa(3);
CI=(lambdamax-3)/2;
CR=CI/0.58;
printf('\nlambdamax at level 2 for the wrt factor A %f,
lambdamax)
printf('\nconsistency ratio for comparison of the factors wrt
factor A is %f, CR)
//comparison matrix for level2(with respect to the factor B
xb=[1 7 1/5;1/7 1 1/8;5 8 1];
sb(1)=0;sb(2)=0;sb(3)=0;
fori=1:3;
for j=1:3;
sb(i)=sb(i)+xb(j, i);
end
end
fori=1:3;
for j=1:3;
xb(j, i)=xb(j, i)/sb(i);
end
end
wb(1)=0;wb(2)=0;wb(3)=0;
fori=1:3;
for j=1:3;
wb(i)=wb(i)+xb(i, j);
end
end

end
wb(i)=wb(i)/3;
end
lambdamax=wb(1)*sb(1)+wb(2)*sb(2)+wb(3)*sb(3)
CI=(lambdamax-3)/2;
CR=CI/0.58;
printf('\nlambdamax at level 2 for the wrt factor B %f,
lambdamax)
printf('\nconsistency ratio for comparison of the factors wrt
factor B is %f, CR)
xc=[1 8 6;1/8 1 1/4;1/6 4 1];
sc(1)=0;sc(2)=0;sc(3)=0;
fori=1:3;
for j=1:3;
sc(i)=sc(i)+xc(j, i);
end
end
fori=1:3;
for j=1:3;
xc(j, i)=xc(j, i)/sc(i);
end
end

wc(1)=0;wc(2)=0;wc(3)=0;
fori=1:3;
for j=1:3;
wc(i)=wc(i)+xc(i, j);
end
wc(i)=wc(i)/3;
end
lambdamax=wc(1)*sc(1)+wc(2)*sc(2)+wc(3)*sc(3)
CI=(lambdamax-3)/2
CR=CI/0.58
xd=[1 5 4;1/5 1 1/3;1/4 3 1];
sd(1)=0;sd(2)=0;sd(3)=0;
fori=1:3;
for j=1:3;
sd(i)=sd(i)+xd(j, i);
end
end
fori=1:3;
for j=1:3;
xd(j, i)=xd(j, i)/sd(i);
end
end
wd(1)=0;wd(2)=0;wd(3)=0;
fori=1:3;
for j=1:3;
wd(i)=wd(i)+xd(i, j);
end
wd(i)=wd(i)/3;
end
lambdamax=wd(1)*sd(1)+wd(2)*sd(2)+wd(3)*sd(3)
CI=(lambdamax-3)/2
CR=CI/0.58
disp(CR)
adjwa=wg(1)/(wg(1)+wg(2)+wg(3)+wg(4))
adjwb=wg(2)/(wg(1)+wg(2)+wg(3)+wg(4))
adjwc=wg(3)/(wg(1)+wg(2)+wg(3)+wg(4))
adjwd=wg(4)/(wg(1)+wg(2)+wg(3)+wg(4))
x=adjwa*wa(1)+adjwb*wb(1)+adjwc*wc(1)+adjwd*wd(1)
y=adjwa*wa(2)+adjwb*wb(2)+adjwc*wc(2)+adjwd*wd(2)
z=adjwa*wa(3)+adjwb*wb(3)+adjwc*wc(3)+adjwd*wd(3)
printf('composite weight for A %f\n', x)

```

```
printf('composite weight for B %f\n', y)
```

```
printf('composite weight for C %f\n', z)
```

### Output of the result

Enter the comparison matrix for the criterion [1 5 3 7;1/5 1  
1/3 5;1/3 3 1 6;1/7 1/5 1/6 1];

lambdamax at level 1 4.341409

consistency ratio for comparison of the factors wrt goal is  
**0.126448**

lambdamax at level 2 for the wrt factor A **3.245477**

consistency ratio for comparison of the factors wrt factor A  
is **0.211618**

lambdamax at level 2 for the wrt factor B **3.412413**

consistency ratio for comparison of the factors wrt factor B  
is 0.355528

consistency ratio for comparison of the factors wrt factor C  
is 0.2116180

consistency ratio for comparison of the factors wrt factor B  
is 0.1132911

composite weight for A **0.666367**

composite weight for B **0.136193**

composite weight for C **0.197440.**

### 3. Conclusion

Input for the program will be only the comparison matrix entered by the user according to his/her preference. The comparison matrices for the alternative with respect to criterions will be given by the experts in the field. Here as the composite weight for A is more followed by C and B, the best alternative is A. The manual results and the programming result matches. However modifications in the program can be made according to the number of criterion and alternatives.

### References

- [1] Saaty, T.L. (1977). A Scaling Method for Priorities in Hierarchical Structures, Journal of Mathematical Psychology, 15: 57-68.
- [2] Saaty, T.L. (1980). The Analytic Hierarchy Process. McGraw-Hill International, New York, NY, U.S.A.
- [3] Saaty, T.L. (1983). Axiomatic Foundations of the Analytic Hierarchy Process, Management Science, 32: 841-855.
- [4] Saaty, T.L. (1990). An Exposition of the AHP in Reply to the Paper 'Remarks on the Analytic Hierarchy Process', Management Science, 36: 259-268.
- [5] Saaty, T.L. (1994). Fundamentals of Decision Making and Priority Theory with the AHP. RWS Publications, Pittsburgh, PA, U.S.A.
- [6] Triantaphyllou, E., and Mann, S.H. (1989). An Examination of the Effectiveness of Four Multi-Dimensional, Decision-Making Methods: A Decision-Making Paradox. International Journal of Decision Support Systems, 5:303-312.
- [7] Triantaphyllou, E., Pardalos, P.M., and Mann, S.H. (1990a). A Minimization Approach to Membership, Evaluation in Fuzzy Sets and Error Analysis, Journal of Optimization Theory and Applications, 66: 275-287