











**Figure 9:** Eye diagrams of 120Gbps DWDM system with equal channel spacing of 100 GHz with optical span of 100 km in the presence of FWM.

## 5. Conclusion

An implementation of 120Gbps DWDM system in the presence of Four Wave Mixing (FWM) with equal channel spacing has been evaluated to estimate Q-factor, BER and FWM power. System performance is increased and the BER is decreased because of reducing the FWM by using the Hybrid Modulator technique. The single and combined effect of various parameter such as effective area, input power, channel spacing and fiber length have been analyzed to determine the effectiveness of FWM power. The combined of four parameter i.e., increasing the effective area, decreasing the input power, increasing the fiber length, and increasing the channel spacing gives the best reduction on the FWM power. The FWM power is reduced as -100dBm. By reducing the FWM, the system performance is increased and also communicates long distances with high data rate.

## References

- [1] Rekha Mehra, Abhimanyu Joshi, "Suppression of Four Wave Mixing in 8 Channel DWDM System Using Hybrid Modulation Technique", International Journal of Electronic and Electrical Engineering, pp. 97-108, 2014.
- [2] Jameel Ahmed, Ashiq Hussain, M.Y. Siyal, Habibullah Manzoor, Abdullah Masooda, "Parametric analysis of four wave mixing in DWDM systems", Optik, vol. no (125), pp.1853– 1859, 2014.
- [3] Haider J. Abd, M.H. Al-Mansoori, N.M. Din, F. Abdullah, H.A. Fadhil, "Priority-based parameter optimization strategy for reducing the effects of four-wave mixing on WDM system", Optik, vol.no (125), pp. 25-30, 2014.
- [4] Joseph Zacharias, Vidya M.S, Vijayakumar Narayanan, "Four-Wave Mixing Suppression by Combining Phase Modulation and Dispersion Management with Data Rates Up to 10 Gbps", International Conference on Control Communication and Computing, pp.157-161, 2013.
- [5] Vishal Sharma, Ramandeep Kaur, "Implementation of DWDM system in the presence of four wave mixing

- (FWM) under the impact of channel spacing", Optik, vol. no (124), pp. 3112-3114, 2013.
- [6] S.Sugumarani, P.Arulmozhivarman, "Effect of Chromatic Dispersion on Four-Wave Mixing in WDM systems and its suppression", IEEE International conference, 2013.
- [7] Haoran Cheng, Wei Li, Youwen Fan, Zhaoyong Zhang, ShaohuaYu, ZhuYang, "A novel fiber nonlinearity suppression method in DWDM optical fiber transmission systems with an all-optical pre-distortion module", optics communications, pp. 152-157, 2013.
- [8] H.J. Abed, N.M. Din, M.H. Al-Mansoori, H.A. Fadhil, F. Abdullah, "Recent four-wave mixing suppression methods", optic, pp. 2214-2218, 2013.
- [9] Gouri Deshmukh, Santosh Jagtap, "Four Wave Mixing In DWDM Optical System", International Journal of Computational Engineering Research, 2013.
- [10] Rajneesh Kaler, R.S. Kaler, "Investigation of four wave mixing effect at different channel spacing", Optik, vol. no (123), pp. 352–356, 2012.
- [11] M. Noshada, A. Rostamia, "FWM minimization in WDM optical communication systems using the asymmetrical dispersion-managed fibers", Optik, pp. 456-460, 2011.
- [12] Amarpal Singh, Ajay K. Sharma, T.S. Kamal, "Investigation on modified FWM suppression methods in DWDM optical communication system", Optical Communication, vol. no (282), pp. 392–395, 2008.
- [13] Gurmeet Kaur, M.L. Singh, "Effect of four-wave mixing in WDM optical fiber systems", Optik, vol. no (120), pp. 268–273, 2007.
- [14] Takahiro Numai & Ouichi Kubota 2000, "Analysis of repeated unequally spaced channels for FDM lightwave systems", J. Lightwave Technology, vol. no (18).
- [15] Forghieri, F, Tkach, RW, Chraplyvy, AR & Marcuse, D, "Reduction of four-wave mixing crosstalk in WDM systems using unequally spaced channels", IEEE Photonic Technology Letter, vol. no (6), pp. 754–756, 1994