

Physico-Chemical Analysis of Sugar Mill Effluent of Kabirdham (C.G.)

Chhaya Bhatt¹, Dr. Rashmi Verma²

¹Research Scholar Department of Chemistry

²Assistant Professor Department of Chemistry

Dr. C.V. Raman University Kargi Road Kota Bilaspur University (C.G.)

Abstract: Industrial waste encompasses the full range of unwanted substances and losses generated by industrial activities, including emissions to air or surface water and In addition, sugar factory effluent discharged in the environment poses a serious health hazard to the rural and semi-urban populations that use stream and river water for agriculture and domestic purposes. Sugar industry is being an important player in foreign exchange earnings and also plays its part in polluting the environment with its discharge. Use of industrial effluent in the land of irrigation has become common practice in India. The present study was aimed to investigate the physicochemical analysis of sugar mill effluent of Bhoramdev co-operative sugar factory Kabirdham. The various parameters studied were colour, odour, temperature, pH, total hardness, turbidity, iron, chloride, sulphate, fluoride ions, total dissolved solids, BOD, COD, calcium, magnesium. In this paper I have discussed different parameters in which permeable limit of some parameters are above compared to BIS limit.

Keyword: Sugar Mill Effluent, Physicochemical Characteristic, BIS

1. Introduction

Sugar industry is a seasonal Industry operating for maximum of 4-5 month in one season. India is the largest producer of sugarcane in the world. Sugar production processing requires huge water for a number of steps and released almost equal quantity of effluent which contains toxic material. There recent studies have indicated that the effluent discharge from sugar consist of a number of organic and heavy metal pollutant in dissolved or suspended form that can bring about changes in the physical, chemical & physiological sphere of the biota. The effluents of industries has ultimate disposal in agriculture field [Sharma RK, et al (2007)]. The sugar mill effluents are having high amounts of suspended solids [Loska K, Wicchula D & Korus I (2004)]. The continuous use of these industrial effluents sewage sludge on agricultural land has become a common practice in India. Toxic elements present in effluent accumulate in the soil and induce a potential contamination of food chain and endanger the ecosystem safety and human health. Waste water from sugar mills with its high BOD, COD and TDS rapidly depletes available oxygen when discharged into water bodies and have adverse impact on aquatic life [Sharma R. K, et al (2007)]. In general, sugar mill effluents contain acidic and alkaline compounds, a significant concentration of suspended solids and a high BOD, COD, and sugar concentration the objective of the study is to determine the physico-chemical characteristics of the effluents of the sugar mill.

2. Materials and Method

Sampling Site: The Bhoramdev sugar factory is situated in Ramhepur which is at the 12 km distance from Kawardha.

Collection of Sample: The effluent samples were collected in pre-cleaned, air tight plastic containers of one liter capacity. From the point of disposal from a Ramhepur

sugar mill. The collected effluent was stored at 4°C to maintain its original characteristics.

3. Analysis Method

[1] Physico-chemical analysis of effluent and their method

The pH, electrical conductivity (EC) and temperature were measured by the method of pH meter, electrical conductivity meter and thermometer respectively. The analysis was carried out in the laboratory by using the procedures given by APHA. Using titrimetric methods, the analysis of chloride (Cl⁻), Magnesium, Calcium and total hardness as CaCO₃ (TH) was performed. While nitrate, iron and sulphate were analyzed by spectrophotometric method. The biological oxygen demand (BOD), which is the amount of oxygen required by microorganisms to stabilize biologically decomposable organic matter under aerobic condition, indicates the amount of biologically degradable organic matter in the wastewater. The BOD of the wastewater samples were measured by titration method. The chemical oxygen demand (COD) measures the amount of oxygen required for oxidation of organic compounds present in wastewater by means of chemical reactions involving oxidizing substances such as potassium dichromate and potassium permanganate. And many more parameters such as colour, odour, and turbidity were determined in this paper.

4. Result and Discussion

The present study was the physico-chemical characteristics. Some of physico-chemical parameters of the effluent were found to exceed those permissible by the Bureau of Indian Standards (BIS). Overall the parameters were found on the higher side of the pollution levels and hence proper treatment methods are advised before the industrial effluents are released to the sewage. The data of industrial effluent of different physico-chemical parameters are presented in table -1

Table 1: Physico-chemical parameters of effluent

Parameter	Unit table	Accepted limit BIS for drinking	Permeable limit in the absence of alternate source BIS (for drinking water)	Remark
Colour	-	-	-	Brown
Odour	-	Unobjectable	Unobjectable	Unpleasant
Temperature	^o C	-	-	29
pH	-	6.5-8.5	Not rejectable	6.3
Total hardness	mg/l	300	600	200
Turbidity	NTU	1	0.5	76.1
COD	mg/l	200	300	405
BOD	mg/l	300	400	275
TDS	mg/l	500	2000	565
Cl ⁻	mg/l	250	1000	63.9
F ⁻	mg/l	1.0	1.5	0.0
NO ₃ ⁻	mg/l	45	100	132
SO ₄ ²⁻	mg/l	200	400	70
Fe	mg/l	0.3	1.0	5.00
Ca ²⁺	mg/l	75	200	65
Mg ²⁺	mg/l	30	100	29

Colour: In the present investigation the colour of the effluent was dark brownish to brown. Colour is very important factor for the aquatic life for making food from sun-rays. Photosynthesis activity gets reduced due to dark colouration and affects other parameters like temperature DO and BOD etc.

Odour: Odour affects human beings in a number of ways. Strong, unpleasant or offensive smells can interfere with a person's enjoyment of life especially if they are frequent and persistent. Major factors relevant to perceived odour nuisance are:

In the present study the smell of effluent is decaying molasses smell.

Temperature: Temperature affects chemical, biological reactions in water. In the present study, it varies from 28 to 29.5^oC.

pH: The pH values are in the range 6.5-8. This is in accordance with the Bureau of Indian Standards (BIS) The extreme pH of wastewater are generally not acceptable, as lower pH cause problems to survival of aquatic life.

Total Hardness: The more cations broke up in the water the "harder" the water. In present study the hardness of sample within limits prescribed by BIS.

Total Dissolved Solids: - Total dissolved solid is the measure of total inorganic salts and other substances that are dissolved in water. In the present study The effluents with high TDS value may cause salinity problem if discharged to irrigation water but under BIS.

Chemical Oxygen Demand (C.O.D.): The COD test decides the oxygen required for concoction oxidation of natural matter with the assistance of solid synthetic oxidant. The COD is a test, which is utilized to quantify contamination of local and modern waste. The waste is measured as far as nature of oxygen required for oxidation of natural matter to create carbon dioxide and water in the present study COD value is high within limit.

Biochemical Oxygen Demand (B.O.D.): B.O.D. is characterized as measure of oxygen required by microorganism while settling natural decomposable natural matter in water vigorous conditions. The natural oxidation is moderate procedure. During oxidation the natural toxins are oxidized by certain microorganism into carbon dioxide and water utilizing broke down oxygen. Hence, forth bringing down in broke up oxygen worth is the measure of BOD connection in the present study BOD value.

Chloride (Cl⁻): Chloride is generally present in natural water. The presence of chloride in natural water attributed to dissolution of salt deposits discharge of effluents from chemical industries oil well operations, sewage discharges initiation drainage, and sea water intrusion in coastal area. The concentration values of chloride in the effluent samples 63.9 mg/L.

Sulphate (SO₄²⁻): It is one of the significant dynamic happening in common water. Sulphate might enter characteristic water through weathering of stores. The concentration values of sulphate in the effluent sample 70 mg/L.

Calcium (Ca²⁺) & Magnesium (Mg²⁺): Calcium value is 65 mg/L. & Magnesium value is 29 mg/l with in the BIS limit.

Iron (fe) & nitrate (NO₃²⁻): iron & nitrate value is higher concentration levels within limit they are unfit for irrigation without proper treatment.

5. Conclusion

Bhoramdev co-operative sugar factory Kabirdham is a first sugar mill of Chhattisgarh state. The present investigation has been to assess the physicochemical characteristic of effluent of sugar mill. The result of present study indicates that sugar mill effluent which is discharged to nearby land and used by the farmer for irrigation purposes, may affects the soil properties. Sugar mill effluent has high concentration of sulphur because sulphur is used for refining the juice during sugar manufacturing process which also increases the Sulphur content. There is considerable concern about P being lost from soils and transported to nearby streams. So by the perusal of result we conclude that sugar mill effluent maintains standard for iron, nitrate, TDS, turbidity, COD while discharging its effluent. In this analysis it effects several phenomena such as soil, water & environment etc.

References

- [1] APHA, Standard methods for examination of waste water analysis 20thed.Inc, Washington1998.
- [2] Ayyasamy PM, Yasodha R, Rajakumar S, Lakshmanaperumalsamy P, Rahman PKSM and Lee S, Impact of sugar Factory Effluent on the Growth and Biochemical Characteristics of Terrestrial and Aquatic Plants. Bull environcontamtoxicol. 81, 2008, 449-454.
- [3] Baskaran L, Ganesh KS, Chidambaram ALA and SundaramoorthyP, Amelioration of sugarmill effluent Polluted Soil and its Effect of Greenngam (Vigna radiate L.) Bot. Res.Int.2, 2009, 131-135.s

- [4] Chandra, R., K. Kumar and J. Singh, 2004. Impact of anaerobically treated and untreated distillery effluent irrigation on soil microflora, growth, total chlorophyll and protein content of *Phaseolus aureus*. L. Journal of Environmental Biology, 25: 381-385
- [5] Chopra, A. K. & Pathak, C. (2013). Enrichment and translocation of heavy metals in soil and Spinaceaoleracea grown in sugar mill Effluent irrigated soil. Sugar Tech., 15(1): 77–83.
- [6] Hulugalle P., M. Pons and S. Sumathi, 2004. Uranium uptake by immobilized cells of *Pseudomonas* sp. strains EPS 5028, *Bacillus* sp. and *Micrococcus* sp. Applied Microbiology and Biotechnology, 39: 661-665.
- [7] Kisu GC, Barman SC, Bhargava SK (2000) Contamination of soil and plants potentially toxic elements irrigated with mixed industrial effluent and impact in the environment. Water Air Soil Pollut., 120: 121- 137.
- [8] Kumar, V. & Chopra, A. K. (2010). Influence of sugar mill effluent on physico-chemical characteristics of soil at Haridwar (Uttarakhand), India. J.of Appl. and Nat. Sci., 2(2):269–279
- [9] Laine, M.M. and K.S. Jurgensen, 2007. Effective and safe composting of contaminated soil Journal of Microbiological Methods, 30: 21- 32
- [10] Loska K, Wiechula D, Korus I (2004) Metal contamination of farming soils affected by industry. Environ. Int., 30: 159-165.
- [11] LouisJesudass, L. and Akila, R., Studies on the Physico-chemical characteristics of the sugar factory effluent, Indian J.Env. Prof, Vol 16, No. 11, pp 808-810.
- [12] Mahavi, R. (2005). Biotechnology application to environmental remediation in resource exploitation. Current Sci., 97: 6-25.
- [13] Maliwal, G.L., K.P. Patel, K.C. Patel and M.N. Patel, 2004. Pollution studies on sugar mill effluent, physico-chemical properties and toxic metals. Research, 14: 231-238.
- [14] Memon AR, Soomro SA and Ansari AK, Sugar Industry Effluent- Characteristics and Chemical Analysis. J.App.Env.Sci.1, 2006, 152-157.
- [15] Nagaraju, M., G. Narasimha and V. Rangaswamy 2009. Impact of sugar industry effluents on plant growth activity. International biodeterioration and biodegradation, 63: 1068-1092.
- [16] Parivash, C.W., 2010. Effect of sugar mill effluent on higher plants. Phytochemistry, 13:1341-1346.
- [17] Sanjay KS (2005) Environmental pollution and sugar industry in India its management in: An appraisal. Sugar Tech, 7 (1): 77-81
- [18] Samuel S. and Muthukkaruppan S.M., Physico-chemical analysis of sugar mill effluent, contaminated soil and its effect on seed Germination of Paddy, International journal of pharmaceutical and biological archives, 2(5), 146-147
- [19] Sharma RK, Agrawal. Environ. Safety, 66 M, Marshall F (2007) Heavy metal contamination of soil and vegetables in suburban areas of Varanasi, India. Ecotoxicol: 258-266.
- [20] Shivappa D, Puttaiah ET and Kiran BR, Physico-chemical characteristics of sugar mill Effluents- current scenario in BhadravathiTsluk, Karanataka, India. Jr.of Ind. Poll.Control.23, 2007, 217-221.
- [21] Siddiqui WA and Waseem M, A Comparative Study of Sugar mill Treated and Untreated Effluent- A case Study.Ori. J. of Chem. 28, 2012, 1899-1904.
- [22] Swamy M, Kaushik A, Kadyan BR, Alueu CP (2001) Sugar mill effluent effects on growth photosynthetic pigments of crop plants. Water Air Soil Pollut., 87(6): 39- 46.
- [23] Thamizhiniyan P, Sivakumar PV, Lenin M and SivaramanM, Sugar Mill Effluent Toxicity in Crop Plants. J.of Phytology; 1, 2009, 68-74.
- [24] VijayaragavanM, SureshkumarJ, NatarajanA, VijayaranganP, SharavananS, and PrabharC, Soil irrigation effect of sugar mill effluent on changes of growth and biochemical content of *Raphanus sativus* L. Current botany. 2, 2011, 09-13