

A Systematic Review of Image Based Moving Vehicle Detection Techniques

Gautami Deshmukh¹, Dr. N. J. Uke²

^{1,2}Department of Information Technology, Sinhgad College of Engineering, Vadgaon Bk, Pune, India

Abstract: *Vehicle detection and counting plays an important role in various applications of traffic management. This involves following stages: i) Vehicle detection, ii) Counting the total vehicles in the scene. In this paper, a systematic review on various methods for vehicle detection and counting is given.*

Keywords: Vehicle detection, counting

1. Introduction

Video analysis is a fast-emerging field based on computer vision techniques. It is a key technology to public safety, intelligent transport system (ITS) and for traffic monitoring. The escalating increase of contemporary urban and national road networks over the last three decades emerged the need of efficient monitoring and management of road traffic. Detection of moving objects in video frames is the first step of information and background subtraction is a very popular approach for foreground segmentation. Conventional techniques for traffic measurements, such as sensors or EM microwave detectors are expensive to install, they demand traffic disruption during installation or maintenance, they are bulky and they are unable to detect slow or temporary stop vehicles.

Video surveillance is an important technique to determine and monitor traffic and ensure safety. In the recent years, traffic monitoring has become an important aspect as it provides information regarding the vehicle flow in a particular area, average lane share and vehicle speed which can help in transportation planning and traffic control. Vehicle flow or vehicle density in a particular area is the most important parameter; hence research on the various techniques of vehicle flow estimation is required to improve the accuracy rate and efficiency. Frequently used vehicle detection techniques are background subtraction, optical flow method, temporal differencing, trajectory based and statistical methods. Apart from these methods, mean shift method, edge detection method and color space model based detection are some other methods used to detect the moving vehicles.

2. Review of Vehicle Detection Techniques

In the literature, there are many models for moving vehicle detection. The most common and widely used model is the background subtraction model.

Background subtraction techniques: Background subtraction is particularly a commonly used technique for detecting moving vehicles. It is used to detect moving regions by subtracting the current image pixel-by-pixel from a reference background image that is created by averaging images over time in an initialization period. The pixels where the difference is above a threshold are classified then

as foreground. The reference background is updated with new images over time to adapt to dynamic scene changes as in case of videos.

Another method for background subtraction is the median based method. Assuming that background is more likely to appear in the scene, the median of the previous „n“ frames is used as the background model. The median is calculated by first sorting all the pixel values from the surrounding neighborhood into numerical order and then replacing the pixel being considered with the middle pixel value [1]. The main advantage of this method is that it handles slow movements of the objects. But this method cannot differentiate between noise and fine details of the image and removes the details along with the noise. Also, it uses a global threshold for all the pixels in the image which is not feasible.

The most widely used background subtraction method is the Gaussian mixture model based method. A Gaussian Mixture Model (GMM) is a parametric probability density function which is represented as a weighted sum of Gaussian component densities. Instead of modeling the values of all the pixels as one particular type of distribution, the pixel is modeled as a mixture of Gaussian. Based on the parameters such as mean, weight and the variance of each of the Gaussians of the mixture, it is determined whether it corresponds to background colors or foreground. Each time the parameters of the Gaussians are updated, the Gaussians are evaluated using a simple heuristic to hypothesize which are most likely to be part of the “background process.” Pixel values that do not match one of the pixel’s “background” Gaussians are grouped using connected components [2].

In[3], an improvised background subtraction technique is used to detect the moving vehicles. It works for real time tracking and also solves the problems of shadow detection using chromatic color representation. A connected component labeling technique is introduced after background subtraction to label the different objects so as to bifurcate between the two objects and each region is labeled with the different label values.

Bhaskar et.al [4] have used a combination of Gaussian mixture model (GMM) and blob detection to detect the moving vehicles from a video. GMM is used to separate the foreground and background from the image. The output of

GMM is the foreground pixels which are then grouped in the current frame using contour detection algorithm. This result in disconnected classes of pixels called the Candidate blob (CB). The positions of the CB, in current frame, is compared using the k-Means clustering that detects the centers of clusters. The input samples CB are then grouped around the clusters to identify the vehicles in each region.

Frame differencing is another method to find the moving object by finding the difference between two consecutive frames. But the disadvantage of this method is it is sensitive to noise. In [5], a combination of the frame differencing method and the background subtraction method is used to get more accuracy. In this model, the system automatically chooses between FDM and background subtraction as the condition arrives

Statistical technique: The basic background subtraction (BBS) model faces problems of illumination changes in case of dynamic background. To overcome this, in[6][7] a pixel intensity based background subtraction (PIBB) technique is used. In this method, first the background modeling is done based on the pixel intensities in the initial frames iteratively. Then once a background model is obtained, the pixel intensities from modeled frame are subtracted from the corresponding current frame pixels to obtain a difference frame. Adaptive threshold is used to classify the pixel as foreground or background pixel. The background model is updated with each upcoming foreground frame so as to avoid the illumination changes.

Optical flow based method: Optical flow methods make use of the flow vectors of moving objects over time to detect moving regions in an image. They motion in video sequences even from a moving camera can also be detected. In[8], first the video frame is converted into gray scale image to avoid the intensity changes. The optical flow estimation is done after this. The optical flow describes the direction and time rate of pixels in a time sequence of two consecutive images[8]. A two dimensional velocity vector, carrying information on the direction and the velocity of motion is assigned to each pixel in a given place of the picture. The result of optical flow estimation gives various objects in the scene. Blob analysis is then performed to obtain the vehicles depending upon the blob size from the objects detected.

In[9], the mean shift method is used to detect the moving vehicles. In this method, initially an object mask is obtained using the adaptive Gaussian mixture model. Then the original mask is improved by using mean shift(MS) segmentation. The holes will be filled and the object boundary will be better aligned with true object boundary.

Trajectory based method: Trajectory based methods are used to detect moving vehicles. One of the methods based on trajectory is used by[10], a set of candidate object locations is generated and an initial set of points that can vote for possible object centers via a regression step is generated. Dense moving points from the video are extracted which further vote for object centers.

Color and texture based vehicle detection: Color and texture are two most important attributes in image processing application. Visual color contrast is used to filter information

present in each color component and to distinguish among similar gray-scale intensities. The color of the road is homogenous and they have the same texture throughout. You can easily detect vehicles making use of this fact. The color of the vehicle will show a huge variation when compared with the color of the road. But problem comes when the color of the vehicle is similar to the color of the road which can be solved by taking the texture into account[11]

Head light detection: During night time, the detection of vehicles become difficult as the brightness is low and the colors are not distinctly visible. Therefore different technique is used to detect vehicles at night time. This technique uses the headlights of the vehicles to detect the vehicle distinctly. A fast segmentation process based on an adaptive threshold is applied to effectively extract bright objects of interest. The extracted bright objects are then processed by a spatial clustering and tracking procedure that locates and analyzes the spatial and temporal features of vehicle light patterns, and identifies and classifies moving cars and motorbikes in traffic scenes [12].

3. Vehicle Counting Techniques

Vehicle counting is required to draw an estimate about the number of vehicles in a particular region.

Every vehicle has its own trajectory. In [13], an approach for counting vehicles is proposed by tracking feature points in the scene and clustering their trajectories into separate vehicles. If there is only a single vehicle path in the traffic scene, feature points into objects according to the estimated average vehicle sizes. In this method, trajectory clusters are assigned into different paths and connected by integrating multiple cues, including the spatiotemporal features of trajectories, the spatial distributions of vehicle paths, and the models of sources and sinks.

In [14], a simple method to count the total number of vehicles is used. In this approach, the centroid or the center of mass of each detected vehicle is found. The total count of vehicles is the total number of centroids.

In[15], an imaginary line is drawn on the video. Whenever the vehicle crosses this line, the count is incremented.

Most of the vehicle counting techniques used the centroid of the vehicle to count the total number of vehicles present.

4. Conclusion

In this paper, various methods for vehicle detection and counting are discussed. The most widely used method for vehicle detection is the background subtraction method as it is easy to implement and the computational load is also less. But the background subtraction method has disadvantage as it gets affected due to sudden illumination changes. Hence background subtraction method is combined with other methods to get better results. The optical flow method gives accurate result but it has great computational load.

References

- [1] S. M. Dhanya, "Survey on Background Identification Using Various Algorithms," vol. 4, no. 01, pp. 222–225, 2015.
- [2] C. Stauffer and W. E. L. Grimson, "Adaptive background mixture models for real-time tracking," *Proceedings. 1999 IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit. (Cat. No PR00149)*, vol. 2, pp. 246–252, 1999.
- [3] M. Anandhalli and V. P. Baligar, "Improvised approach using background subtraction for vehicle detection," *2015 5th IEEE Int. Adv. Comput. Conf. IACC 2015*, pp. 303–308, 2015.
- [4] P. K. Bhaskar and S.-P. Yong, "Image processing based vehicle detection and tracking method," *2014 Int. Conf. Comput. Inf. Sci.*, pp. 1–5, 2014.
- [5] W. Hossain and M. N. Das, "Moving Object Detection in Dynamic Backgrounds for Surveillance Systems," no. 978, pp. 1476–1479, 2014.
- [6] D. K. Yadav, L. Sharma, and S. K. Bharti, "Moving Object Detection in Real-Time Visual Surveillance using Background Subtraction Technique," no. 1, pp. 79–84, 2014.
- [7] K. K. Hati, P. K. Sa, and B. Majhi, "Intensity Range Based Background Subtraction for Effective Object Detection," vol. 20, no. 8, pp. 759–762, 2013.
- [8] Y. Chen, "Moving Vehicle Detection Based on Optical Flow Estimation of Edge," pp. 754–758, 2015.
- [9] S. Zhang, C. Wang, S. C. Chan, and X. G. Wei, "New Object Detection , Tracking and Recognition Approaches for Video Surveillance over Camera Network," no. c, pp. 1–12, 2014.
- [10] M. Zhai, L. Chen, J. Li, M. Khodabandeh, and G. Mori, "Object Detection in Surveillance Video from Dense Trajectories," pp. 12–15, 2015.
- [11] R. Mejía-iñigo, M. E. Barilla-pérez, and H. A. Montesvenegas, "Color-based Texture Image Segmentation for Vehicle Detection," no. 2006, 2009.
- [12] G. Salvi, "An automated nighttime vehicle counting and detection system for traffic surveillance," *Proc. - 2014 Int. Conf. Comput. Sci. Comput. Intell. CSCI 2014*, vol. 1, pp. 131–136, 2014.
- [13] R. Zhao and X. Wang, "Counting vehicles from semantic regions," *IEEE Trans. Intell. Transp. Syst.*, vol. 14, no. 2, pp. 1016–1022, 2013.
- [14] R. Javadzadeh, E. Banihashemi, and J. Hamidzadeh, "Subtraction Technique and Prewitt Edge Detection," vol. 6, no. 10, pp. 8–12, 2015.
- [15] G. N. Swamy and S. Srilekha, "Vehicle Detection and Counting Based on Color Space Model," pp. 447–450, 2015.